



GENERAL INFORMATION PORR SLAB TRACK DECISION-MAKING OF SLAB TRACK SYSTEM IN AUSTRIA



Langenlebarn - First Installation PORR Slab Track System in 1989

Heaviest operated track (ÖBB Western Railway Line) approx. 1,4 billion gross tons to date (25 tons axle load).

Construction

(space requirements, reduced self weight)

Method and Maintenance


(track laying precision, rapid installation, ease of replacement)

Quality


(prefabrication, decreased noise emission, high ride quality)

Cost-Effectiveness


COMPONENTS



COMPONENTS





TYPE OF STRUCTURE



Applicability for viaducts


Applicability for at-grades sections





Applicability for **tunnels** sections

MODULAR EQUIPMENT COMPONENTS







SPEED AND TRACK ACCURACY HS2 IN THE UK

Record speed requirements for a railway line in Europe

- 360 km/h operating speed
- 400 km/h design speed

early award of contract for slab track design and supply

- reduce interface risks
- structure design fit for purpose

Design & Supply









SPEED AND TRACK ACCURACY HS2 IN THE UK

PORR/VCE challenges and approach

- Design stage:
 - design optimization (clearance)
 - interface management (fit for purpose)
 - Weight & material reduction (lower self-weight)
 - Information Modelling (AIM instead BIM)
- Execution stage:
 - precision in slab prefabrication
 - Concrete mix design and components specifications
 - Excellence and precision in construction



HIGH SPEED TRACK VDE 8.2 IN GERMANY

• 300 km/h operating speed

Total length 188km double track
25 tunnels (55 km / 29 %)
32 bridges (27 km / 14 %)
earthworks (106 km / 56 %)

-> Full operation since 12/2015

Design & Supply & Build
















HIGH SPEED RECORD VDE 8.2 IN GERMANY

- Successful DB test drives on the PORR Slab Track Austria VDE 8.2 high speed line in Germany
- Record speed of 405 km/h
- 300 km/h operational and 330 km/h design speed
- high quality after 10 years of operation




SPACE CONSTRAINTS KORALMBAHN IN AUSTRIA

Challenges:

- Space constraints (small tunnel diameter combined with the length of 2x33 km in twin bores
- Extensive N&V attenuation requirements
- Manholes for drainage in the middle of the track

Solutions

- STA slabs with reduced width (212 cm)
- reduced/optimized construction height
- combined Mass-Spring-System (MSS) with integrated STA technology
- Rapid installation enabled by a high degree of prefabrication



SPACE CONSTRAINTS KORALMBAHN IN AUSTRIA - SYSTEM DEVELOPMENT

typical design

improved design

Mass Spring System - Trough

Regelquerschnitt ZV Nordröhre mit L-MFS 3,5t/m - 20Hz

M.:1:25

S. GIP, b=2.10m

TROC bewehrt

LACHENAGER

ASSERUNGSKANALE o~25m

FILTERBETON 10.0 139.0 106.0 2.0 36.0

O(A) 16/32mm

PRAINAGEMATI

Detail A


2.85 m

Submision 2007

25% Reduction in system width

>Tunnel tolerances -17 cm

< Alignment changes -71 cm Mass Spring System -Slab




Execution 2020

SPACE CONSTRAINTS KORALMBAHN IN AUSTRIA - SYSTEM DEVELOPMENT

typical design

Mass Spring System <15 Hz



Submision 2007


"from fixed to flexible"

Less alignment changes no special tunnel shapes flexible N&V adjustments

> < System height -38.5 cm

improved design

Mass Spring System <15 Hz



Execution 2020

VALUE ADDED APPROACH METRO TUNNEL MELBOURNE


- **Broad gauge** proven STA system tailored to the **local specifications**
- Integrated derailment containment cost reduction
- Complex N&V requirements urban environment
- Prefabricated mass spring systems reduction construction time
- Different CAD System

Design & Supply & Supervision











VALUE ADDED APPROACH DELHI-MEERUT IN INDIA

- **standard gauge** proven STA system tailored to the **local specifications**
- Integrated derailment containment cost reduction
- Installed throughout on bridges, earthworks and in tunnels
- Slab Track Austria system supply for
 - mainline
 - turnouts
 - diamond crossings

Systemdesign & supervision (prod./inst)











VALUE ADDED APPROACH DOHA METRO, QATAR

- Metro Application proven STA system tailored to the local specifications
- Very complex interfacing processes with the civil contractors (7 different packages)
- Installed throughout on bridges, earthworks and in tunnels
- Complex N&V requirements urban environment leads up to >20km Mass Spring Systems
- BIM from day one

Design & Supply & Build









INSTALLATION W/O RAIL STUTTGART 21

- slab track completion before final rail delivery
- Slab track installation for the entire length of the 33 km in tunnel had to be done without the final rail
- High precision of key points on the precast slab enabled rail-free installation at high quality






ASPHALT BASE LAYERSTUTTGART 21

Design approach - addressing challenges of previous asphalt abase layer application and providing improvements


- Asphalt mix was modified for longer durability
- The asphalt layer was covered on sides and it is fully covered under the slab
- Asphalt layer without strict tolerance for application (compensated by the SCC)
- Strong asphalt-SCC bond no connection or shear dowels needed



SLAB TRACK AUSTRIA BENEFITS

- modular system for every environment
- industrialized construction quality and speed
- **Efficient on-site** assembly
- **High precision** under complex conditions
- Early system choice in planning saves costs.
- Decades of proven performance

"Ready to take on new design challenges"





GET IN TOUCH

IF YOU HAVE ANY QUESTIONS, PLEASE DON'T HESITATE TO CONTACT US.

Vlad Metaxa



T +43 50 626 5705

M +43 664 626 1304 (Europe)

M +974 6610 0325 (Middle East)

vlad.metaxa@porr.at

Slab Track Austria - slabtrackaustria.com

Rudolf Felsner



T +43 1 897 53 39 1142

M +43 664 824 30 57

felsner@vce.at

www.vce.at